



8 PORT FIBER OPTIC FTTX BOX - IP65 - 3 IN 8 OUT

07IP65V1-8PE1E



Overview

Fiber access termination box is able to hold up to 8 subscribers. It is used as a termination point for the feeder cable to connect with drop cable in FTTx network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

Applications

- Telecommunication Network
- CATV-Cable Television
- Outdoor wall mount, FTTH, FTTx, GPON

Features

1 inputs (12.00mm) can use multi-fiber cable or uncut cable, 3 In and 8 outputs for FTTH, convenient fast to operate.

The fiber bending radius minimum is 20mm.

Unique design of separate covers for the adapter and cable entry/exit ports to makes it more safety, nice and humanity, both cover is removable.

All the materials are non toxic and dermatologically safe, can last long for more than 20years.

Plastic material is flame retardant, metal parts is steel stainless AISI-303 and resistant to the corrosion in normal temperature, can be test ok in different facilities.

Specification

Color	White
Dimension (A*B*C) mm	210*160*47mm
Max. Capacity	8 cores
Max. Adapter	8 pcs SC simplex
PLC Splitter	1:8
Accessory	PC+ABS, - IP65
Weight	0.65kg

Pictures for reference

