



# 24 PORT FIBER OPTIC FTTX BOX - IP65 - 2 IN 2 OUT

FTTH, FTTx, GPON



## Overview

Fiber access termination box is able to hold up to 24 subscribers. It is used as a termination point for the feeder cable to connect with drop cable in FTTx network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

## Applications

- Telecommunication Network
- CATV-Cable Television
- Wall-Mounted, Pole-Mounted, Aerial Application
- FTTH, FTTx, GPON

## Features

- 2 inputs can use multi-fiber cable or uncut cable, 2 out puts for FTTH, convenient fast to operate.
- The fiber bending radius minimum is 20mm.
- Unique design of separate covers for the adapter and cable entry/exit ports to makes it more safety, nice and humanity, both cover is removable.
- All the materials are non toxic and dermatologically safe, can last long for more than 20years.
- Plastic material is flame retardant, metal parts is steel stainless AISI-303 and resistant to the corrosion in normal temperature, can be test ok in different facilities.

## Specification

Color	Gray
Dimension (A*B*C) mm	270*235*90 mm
Max. Capacity	48 cores via lc dx adapter
Max. Adapter	24 pcs SC simplex
PLC Splitter	1x2,1x4,1x8, 1x16 mini splitter
Material	PC+ABS, - IP55
Weight	0.800 kg

## Pictures for reference

