



# 16 PORT FIBER OPTIC FTTX BOX -IP66 - 4 IN 16 OUT



## Overview

Fiber access termination box is able to hold up to 16 subscribers. It is used as a termination point for the feeder cable to connect with drop cable in FTTx network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

## Applications

- Telecommunication Network
- CATV-Cable Television
- Wall-Mounted, Pole-Mounted, Aerial Application
- FTTH, FTTx, GPON

## Features

- Water-proof design with IP-55 Protection level.
- Integrated with splice cassette and cable management rods.
- Manage fibers in a reasonable fiber radius condition.
- Easy to maintain and extend the capacity.
- Fiber bend radius control more than 40mm.
- Suitable for the fusion splice or mechanical splice.
- 2:1\*8 or 1:1\*16 Splitter can be installed as an option.
- Efficient cable management.
- 16 ports cable entrance for drop cable

## Specification

Color	Grey
Dimension (A*B*C) mm	285(H)*175(W)*80(D)mm
Max. Capacity	12 cores
Max. Adapter	8 pcs SC simplex
PLC Splitter (Max)	1:16
Accessory	PC+ABS, - IP65
Weight	1000g

## Pictures for reference

