

16 PORT FIBER OPTIC FTTX BOX -IP66 - 4 IN 16 OUT



Overview

Fiber access termination box is able to hold up to 16 subscribers. It is used as a termination point for the feeder cable to connect with drop cable in FTTx network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

Applications

- Telecommunication Network
- CATV-Cable Television
- Wall-Mounted, Pole-Mounted, Aerial Application
- FTTH, FTTx, GPON

Features

- Water-proof design with IP66
- Integrated with splice cassette and cable management rods.
- Manage fibers in a reasonable fiber radius condition.
- Easy to maintain and extend the capacity.
- Fiber bend radius control more than 40mm.
- Suitable for the fusion splice or mechanical splice.
- 2:1*8 or 1:1*16 Splitter can be installed as an option.
- Efficient cable management.
- 16 ports cable entrance for drop cable

Specification

Color	Grey
Dimension (A*B*C) mm	285(H)*175(W)*80(D)mm
Max. Capacity	32 fibers (LC duplex)
Max. Adapter	16 SC SX / 16 LC DX
PLC Splitter (Max)	1:16
Accessory	PC+ABS, - IP66
Weight	1000g

Pictures for reference

